





NOTE: This shed is not wind rated but can achieve wind rating: N2 as per AS4055-2021 with the additional purchase of a frame kit.

If you require a higher wind rating please contact us: admin@absco.com.au or 1800 029 701

When laying concrete slab, ensure there is a rebated edge 25mm deep around the perimeter. This will help water egress from the base of the shed.



#### PLEASE LEAVE A REVIEW

Tell us about your experience!  
Visit [www.absco.sheds.com.au/review](http://www.absco.sheds.com.au/review)

### GENERAL INSTRUCTIONS

- Before commencing any assembly, read through these instructions in detail to gain a thorough understanding of assembly methods and associated details.
- Unpack the carton and carefully identify and check off all the parts against the parts described and illustrated on "COMPONENTS PACKING LIST" pages.
- Local authority approval must be obtained prior to construction of the shed. Once you have selected your site you will need to lodge a site plan to your local council.

### SITE PREPARATION

- The site for the shed must be level. An uneven surface may result in misalignment of parts.
- The shed shall be erected on top of a reinforced concrete slab and anchored down appropriately illustrated on "FINAL CONSTRUCTION" page. **If using a rebated slab ensure that all frame uprights are trimmed 25mm.**

### TOOLS REQUIRED



### SAFETY NOTES





- Some parts may have sharp edges. It is advisable to wear gloves when handling these items and safety glasses if drilling holes. Sensible shoes are highly recommended.
- Do not erect your shed in windy conditions.
- It is highly recommended to erect the shed with two or more people.
- Do not sit, stand or walk on the roof of your shed.

### RECOMMENDED



## COMPONENT PACKING LIST


















Check off all components.

| QTY | COMPONENT DESCRIPTION                                                                                           | PART NO.   | CHK | QTY | COMPONENT DESCRIPTION                                                                                                 | PART NO. | CHK |
|-----|-----------------------------------------------------------------------------------------------------------------|------------|-----|-----|-----------------------------------------------------------------------------------------------------------------------|----------|-----|
| 6   |  STEEL SHEET<br>2034mm X 773mm | H30        |     | 6   |  STEEL SHEET<br>1546mm X 773mm       | 45A      |     |
| 4   |  STEEL SHEET<br>2034mm X 773mm | H31        |     | 2   |  STEEL SHEET<br>2034mm X 329mm       | H39B     |     |
| 2   |  GABLE L/H<br>L = 1475mm       | 16L        |     | 2   |  GABLE R/H<br>L = 1475mm            | 16R      |     |
| 2   |  RIDGE BEAM<br>L = 1147mm     | 97B<br>L/R |     | 1   |  RIDGE BEAM<br>JOINER<br>L = 450mm | ZARSP    |     |
| 1   |  BRACE<br>L = 393mm          | 13A        |     | 1   | FITTINGS & ACCESORIES<br>PACKET ( SEE PAGE 5)                                                                         |          |     |
| 1   | CHANNEL SET<br>(SEE PAGES 4)                                                                                    |            |     |     |                                                                                                                       |          |     |

Nominal sheet widths are shown. +/- 2mm is within tolerance.







## COMPONENT PACKING LIST

Check off all components.

| QTY                    | COMPONENT DESCRIPTION                                                                                       | PART NO. | CHK | QTY | COMPONENT DESCRIPTION                                                                                        | PART NO. | CHK |
|------------------------|-------------------------------------------------------------------------------------------------------------|----------|-----|-----|--------------------------------------------------------------------------------------------------------------|----------|-----|
| 2                      |  CHANNEL<br>L = 1126mm     | 59EL     |     | 2   |  CHANNEL<br>L = 1126mm     | 59ER     |     |
| 4                      |  CHANNEL<br>L = 1126mm     | 81CL     |     | 4   |  CHANNEL<br>L = 1126mm     | 81CR     |     |
| 1                      |  CHANNEL<br>L = 1496.5mm   | 77BL     |     | 1   |  CHANNEL<br>L = 1496.5mm   | 77BR     |     |
| 1                      |  JAMB<br>L = 1537mm       | 93L      |     | 1   |  JAMB<br>L = 797mm        | 93R      |     |
| 2                      |  JAMB<br>L = 2034mm      | HJ2      |     | 4   |  LIP TRIM<br>L = 1546mm  | 87A      |     |
| <b>NOTCHED CHANNEL</b> |                                                                                                             |          |     |     |                                                                                                              |          |     |
| 1                      |  CHANNEL<br>L = 1496.5mm | 81AL     |     | 1   |  CHANNEL<br>L = 1496.5mm | 81AR     |     |
| 1                      |  CHANNEL<br>L = 1496.5mm | 77CL     |     | 1   |  CHANNEL<br>L = 1496.5mm | 77CR     |     |
| 2                      |  CHANNEL<br>L = 1496.5mm | 78BL     |     | 2   |  CHANNEL<br>L = 1496.5mm | 78BR     |     |
| 2                      |  CHANNEL<br>L = 329mm    | 81M      |     |     |                                                                                                              |          |     |










## COMPONENT PACKING LIST

Check off all components.

| QTY | COMPONENT DESCRIPTION                                                                                                          | PART NO. | CHK | QTY | COMPONENT DESCRIPTION                                                                                                       | PART NO. | CHK |
|-----|--------------------------------------------------------------------------------------------------------------------------------|----------|-----|-----|-----------------------------------------------------------------------------------------------------------------------------|----------|-----|
| 2   |  CAP GABLE                                    | 14A      |     | 1   |  RIDGE PLATE                              | RBP      |     |
| 11  |  CHANNEL JOINER<br>L = 200mm                  | CSJ      |     | 1   |  3mm<br>DRILL BIT                         | DRILL    |     |
| 1   |  8G x 3/8mm SELF TAPPING SCREW<br>220PACK     | FAST 001 |     | 1   |  8G x 3/8mm SELF TAPPING SCREW<br>100PACK | FAST 001 |     |
| 12  |  SELF DRILLING HEX HEAD TEK SCREW 45mm LONG  | FAST 019 |     | 1   |  HEX TEK SCREW DRIVER BIT                | FAST 023 |     |
| 24  |  SELF DRILLING HEX HEAD TEK SCREW 15mm LONG | FAST 035 |     | 1   |  PHILIPS DRIVER BIT                     | FAST 038 |     |
| 1   | ASSEMBLY INSTRUCTION MANUAL                                                                                                    |          |     |     |                                                                                                                             |          |     |


### COMPONENT PACKING LIST

Check off all components.

| HIGH GARAGE FRONT FRAME PACK            |                                                                                                              |             |     |     |                                                                                                                       |                      |     |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------|-------------|-----|-----|-----------------------------------------------------------------------------------------------------------------------|----------------------|-----|
| QTY                                     | COMPONENT DESCRIPTION                                                                                        | PART NO.    | CHK | QTY | COMPONENT DESCRIPTION                                                                                                 | PART NO.             | CHK |
| 2                                       |  CHANNEL<br>L = 2300mm      | C2300       |     | 10  |  CHANNEL<br>L = 285mm               | K0285                |     |
| 2                                       |  CHANNEL<br>L = 2070mm      | N2070       |     | 2   |  CHANNEL<br>L = 240mm               | C0240                |     |
| 2                                       |  CHANNEL<br>L = 2034mm      | C2034       |     | 2   |  CHANNEL<br>L = 100mm               | C0100                |     |
| 2                                       |  CHANNEL<br>L = 1484mm    | M1484       |     |     |                                                                                                                       |                      |     |
| HIGH FRONT FRAME FITTINGS PACK CONTENTS |                                                                                                              |             |     |     |                                                                                                                       |                      |     |
| 10                                      |  MULTI PURPOSE<br>BRACKET | BKT17       |     | 1   |  SMALL<br>TRANGLE PLATE           |                      |     |
| 6                                       |  10mm<br>DYNABOLTS        | FAST<br>015 |     | 150 |  SELF DRILLING<br>16mm TEK SCREWS | PACK<br>WAFER<br>150 |     |
| ROLLER DOOR PACK                        |                                                                                                              |             |     |     |                                                                                                                       |                      |     |
| ROLLER SHUTTER UNIT WITH TRACKS         |                                                                                                              |             |     |     |                                                                                                                       |                      |     |

## Guide on Splitting Sheets

- This product comes with a perforated sheet that is designed to be split into two smaller sheets.
- These sheets have sharp edges. Once separated please use appropriate foot and hand protection when handling.**
- In order to split the sheet lay it on the ground and lift and fold one end until the perforations have cleanly snapped.
- Discard the middle piece as scrap when convenient. Fold the scrap piece in half two or three times and throw in garbage.



Check sheet for perforations




Fold first side of sheet until free



Fold middle section of sheet until free



Discard middle piece


| SPLITTING SHEET 39B |                                                                                                                   |          |   |     |                                                                                                                     |          |
|---------------------|-------------------------------------------------------------------------------------------------------------------|----------|---|-----|---------------------------------------------------------------------------------------------------------------------|----------|
| QTY                 | COMPONENT DESCRIPTION                                                                                             | PART No. |   | QTY | COMPONENT DESCRIPTION                                                                                               | PART No. |
| 1                   |  STEEL SHEET<br>2034mm X 773mm | H39      | = | 2   |  STEEL SHEET<br>2034mm X 773mm | H39B     |

## SNAPTITE ASSEMBLY GUIDE

The SnapTite Assembly System locks end channels to all roof and wall sheets without the need for tools and fasteners.

To assemble each panel, the perimeter channels are secured to the top and bottom of each panel. Gently tap the channel over the SNAPTITE lugs on the sheet, working along the sheet.

Each perimeter channel must finish flush with the edges of the sheets. Simply tap the channel along the sheets until each end is neatly flush. If you need to remove channels from the panels, slide it off from the side.



**SNAPTITE**  
World's Easiest Assembly System  
*UNIQUE PATENTED SYSTEM*

Channel locks the shed panel into position without the need for screws!


## FASTENING SYMBOLS

**SNAPTITE**

Secure channel to sheeting by SNAPTITE fastening method.



Join components together with one screw at this location only, as some channels have extra holes that are not required for this model of shed.



Do not join components together at this location yet, as the screws may obstruct further assembly of the other components.



Join components together by pre-drilling the holes first. Use one component as template to mark where the holes are and drill with a 3mm drill bit.



3mm pop rivet



4mm nut and bolt set.


### Guide on Joining Spliced Channels

The text marked on all parts must be shown on the same side as each other




#### Step 1.

Position the channels and the CSJ joiner so the centre of the CSJ is in line with the end of each channel to be joined together.




#### Step 2.

Join the first channel to the CSJ by inserting the centre of the CSJ, on an angle, to the end of the channel where the JOIN>> text is marked.




Push down one side of the CSJ until you hear a 'click'.



#### Step 3.


Join the second channel to the CSJ by positioning the <<JOIN of the channel at the centre of the CSJ, on an angle. Push the CSJ into the channel until you hear a 'click'.




#### Finished Channel.

The joined channels should now look like the picture with the CSJ positioned equally inside of the joined channels.

Drill out holes with 3mm drill bit in CSJ to match the holes in channel. Drilling of screws on the joined channels is being done after sheets are locked on the spliced channels.




...



## PRE-ASSEMBLY OF SPLICED CHANNELS

Join together 22x channel sections using 11x channel joiners (Part CSJ)


NOTE: Some channels may have holes in them - You will need to redrill holes where CSJ joining channel covers them.




### Guide on Joining a Spliced Ridge Beam

Follow these three steps to assemble a ridge beam.


If present, remove plastic coating from top side of ridge beam capping before assembly.




**Step 1.**  
Place two ridge beams as shown and push them together. Slide the cap of one under the other.



**NOTE.**  
There is a 50mm overlap of the ridge caps when the beams are in position.



**Step 2.**  
Use the ZARSP to connect at the centre of the two ridge beams. Be sure it is pushed in fully.



**Step 3.**  
Turn over the ridge beam. Measure 250mm from the middle along the centre of one ridge beam, mark spacings of 50mm. Fasten with a Tek screw at each marking.





Repeat to the other side of the ridge beam assembly.

**TIP:** Predrilling each hole with the 3mm drill bit makes it easier to fasten.




Finished Spliced Ridge Beam




Finished  
Joined Ridge Beams

## PRE-ASSEMBLY OF SPLICED RIDGE BEAM

1 required.




## OVERVIEW OF ROOF COMPONENTS





## REAR PANEL ASSEMBLY


1 required.



Turn the panel over.  
Fit the two large gables (16L  
& 16R) to the inside face of  
the top channel (77B)



## ROOF PANEL ASSEMBLY

2 required.






## SIDE PANEL ASSEMBLY

2 required.



## HIGH FRONT FRAME ASSEMBLY


STEP 1 of 2



**NOTE: THESE FRAMES WILL NEED TO BE  
TRIMMED 25mm TO FIT REBATE**

## HIGH FRONT FRAME ASSEMBLY

STEP 2 of 2.




NOTE: IF YOU HAVE AN EDGE REBATE IN YOUR CONCRETE SLAB, YOU WILL HAVE TO CUT AN AMOUNT OFF THE BOTTOM OF THE FRAME LEGS EQUAL TO THE DEPTH OF THE REBATE.

## HIGH FRONT FRAME ASSEMBLY SUPPORT PHOTOS


### STEP 1.

Draw pattern on the concrete in accordance with the dimensions detailed in the assembly instructions.


#### Step 1a



#### Step 1b



#### Step 1c




## HIGH FRONT FRAME ASSEMBLY SUPPORT PHOTOS

### STEP 2.

Understand where components are to be positioned.




#### Step 2



## HIGH FRONT FRAME ASSEMBLY SUPPORT PHOTOS

### STEP 3.

Join C0100 to C2034



## HIGH FRONT FRAME ASSEMBLY SUPPORT PHOTOS


STEP 4.

Join C2034 to M1484

### Step 4a



### Step 4b



## HIGH FRONT FRAME ASSEMBLY SUPPORT PHOTOS


### STEP 5.

Join K0285 to C2034 & N2070.

**Step 5a**




**Step 5b**



**Step 5c**




**Step 5d**



**Step 5e**



**Step 5f**




## HIGH FRONT FRAME ASSEMBLY SUPPORT PHOTOS


### STEP 6.

Fit multipurpose brackets.


#### Step 6a



#### Step 6b



#### Step 6c




## HIGH FRONT FRAME ASSEMBLY SUPPORT PHOTOS


### STEP 7.

Assemble the C0240 & C2300 sections.

**Step 7a**




**Step 7b**



**Step 7c**



**Step 7d**



**Step 7e**



## HIGH FRONT FRAME ASSEMBLY SUPPORT PHOTOS

### STEP 8.

Join all sections together.


**Step 8a**



**Step 8b**



**Step 8c**



**Step 8d**



**Step 8e**




## HIGH FRONT FRAME ASSEMBLY SUPPORT PHOTOS


### STEP 9.

Turn over frame and repeat steps 4 to 8.

#### Step 9a




#### Step 9b



## HIGH FRONT FRAME ASSEMBLY SUPPORT PHOTOS


STEP 10.

Fully assembled front frame.



## FRONT PANEL ASSEMBLY

1 required.



Note: The outer edge of the front panel should protrude 20mm past the outer edge of the front frame for corner lapping of side wall panels. (Fig.B)




FIG. B

FIG. A

FIG. A





FIG. B

## HIGH FRONT FRAME DETAILS

Recommended slab dimensions - 3100mm x 2360mm

External wall dimensions - 3000mm x 2260mm


Internal wall dimensions - 2960mm x 2220mm



- Secure multipurpose brackets to uprights using self drilling screws
- Move frames into position, mark and drill holes in slab using 10mm masonry drill bit
- Secure frames to slab with M10 dynabolts.

## PANEL CONSTRUCTION


NOTE: Take care to ensure that all wall panels are not upside down. The top channels of each panel are pre-punched for attaching roof sheeting. The base channels are not.




## ROOF CONSTRUCTION

### STEP 1.

Slide the roof panels into position and secure with only one screw in each corner at this stage.




INSIDE VIEW



### STEP 2.

Secure ridge beam to gable sections with two screws at either end.

INSIDE VIEW





### STEP 3.


After the roof panels have been secured, fit two gable braces (13A) form the top wall channel to the underside of the ridge beam at 45 degrees as shown at the rear wall only.

NOTE: This symbol  denotes that holes to be pre-drilled with a 3mm drill bit before fastening.

**- WARNING -**  
**Do not climb on or walk on the roof.**




### FINAL CONSTRUCTION




Bend the top and bottom flanges as shown, then hook the bottom flanges under the top channel and screw top to the ridge beam with two screws.

### ANCHORING OF SHED



Location of 16  
concrete anchors

Each anchor consists of one nut, bolt, M10 dynabolt and steel angle.  
Drill a 10mm hole into the wall sheet.  
Drill a 10mm hole into the concrete.



\* Denotes hot dip galvanised finish

## ROLLER SHUTTER ASSEMBLY SUPPORT PHOTOS




To begin remove the tape that is holding the back cover of the roller shutter unit.

1  
Take the two "end plate legs" and slide them onto the roller door unit as shown below. These will be used to fit the guides.

2  
Take the guides and slide them up over the edge of the roller shutter and end plate leg.

3  
Pre-drill with the 3mm drill bit through the guide and the end plate legs.  
Take a 45mm long Tek screw and fasten through both of these.  
NOTE: Do not advance the screw all the way down yet because we will use this screw to fasten it to the inside frame of the shed.



### ROLLER SHUTTER ASSEMBLY SUPPORT PHOTOS



4  
Position the roller door inside the shed as shown. You will need to bring it through the opening at an angle to get it to fit. Lay on ground as shown if there is enough floorspace. Remove all protective films at this point.



5  
Stand the unit up and position the roller unit centred in the opening, you can check it is centred by looking at the guides. They should be running parallel to the front frame inset the same distance on both sides.

6  
Next drive the Tek screw that is already in the roller unit through the rest of the way into the front frame on both sides.

7  
Now the roller door is held in place slide the roller down and fasten at each cross member in the front frame. This will result in 4 screws per side. pre-drilling with a 3mm drill bit will make it easier to drive the 45mm tek screw into the front frame.




## ROLLER SHUTTER ASSEMBLY SUPPORT PHOTOS



With the roller shutter fully extended use three more tek screws and fasten inside the roller unit in the top corner at the middle and either side spaced equally.


It is easier if you have an extension for your drill. With the shutter unrolled completely remove the protective polycell sheet from within the roller.




Take the sheet metal cover for the roller unit. Orient as shown, fasten with the supplied pop-rivets or use our most common self tapping screw to fasten.

## ROLLER SHUTTER FINAL ASSEMBLY

The handles can be mounted at any width along the locking bar.  
Critical dimensions for drilling a handle are shown below




Internal view of roller shutter



Fasten with two M4x15mm button hd screws per handle.

The two guides require cutouts to accept the locking bars of the roller shutter. Critical dimensions of the cutout are shown below.




VIEW G

Looking inside the guide track

\*NOTE: If rubber is fitted to the bottom slat then make this dimension 11mm.

An uneven slab or misalignment of parts during construction may mean you have to alter these dimensions to suit.



## Absco Large Gable Roof Shed Notes

### General

- 1.G This instruction manual shall be read in conjunction with other consultants drawings, specifications and written instructions provided by Absco and/or their representatives.
- 2.G The drawings provided herein are for installation and structural engineering purposes only. If discrepancies are discovered within the documentation provided, these shall be brought to the attention of Absco and written approvals obtained prior to commencing the affected section of work.
- 3.G If in doubt ask.
- 4.G Until approvals from the local authorities are obtained, commencement of construction from these drawings shall not commence.
- 5.G Unless varied by the project specification, all materials and workmanship shall be undertaken in accordance with the relevant Australian standards and the by-laws and ordinances of the relevant building authorities.
- 6.G All dimensions indicated in these drawings shall be verified on site by the installation contractor. Scaling of drawings shall not be undertaken.
- 7.G Prior to commencing works on site, the contractor shall verify the position of all services in the area to ensure that the construction does not interfere with any of those services.
- 8.G During installation on site the shed structures shall be maintained in a stable condition with no part becoming overstressed or permanently deformed.
- 9.G In circumstances where the shed has been installed in a manner which is inconsistent with the installation manual, structural certification shall be void.
- 10.G The structural components detailed within this installation manual have been designed for the following loads in accordance with AS/NZS1170 based on a Class 10a, Type 2 structure:
- Roof Live Load: 0.25 kPa uniformly distributed or 1.1 kN concentrated as per AS/NZS1170.1

Wind Load: Classification N2, Non-Cyclonic to AS4055 where  $V_u = 40$  m/s,  $V_s = 26$  m/s

Windward wall  $C_{pe} = 0.7$

Leeward Wall  $C_{pe} = -0.3$  to  $-0.5$  as applicable based on shed geometry

Side Wall  $C_{pe} = -0.2$  to  $-0.65$  as applicable based on shed geometry

Roof  $C_{pe} = -0.3$  to  $-1.04$  depending on wind direction

## Absco Large Gable Roof Shed Notes


### Steelwork

- 1.S All structural steelwork shall have a corrosion protection system applied consistent with AS/NZS 2312-2002.
- 2.S All structural steelwork detailed within this installation manual shall be minimum Grade 550 for roll formed sections (including roof and wall sheeting and portal frame members) and Grade 250 for angle sections.
- 3.S All multi purpose and anchor brackets for connection onto the supporting reinforced concrete slab (includes 45x45x3EA x 34mm long and 47x47x1.9EA x 80 long) shall be minimum Grade 450.
- 4.S All portal frame knee and apex plates shall be minimum Grade 450
- 5.S All roof, and wall sheeting shall be minimum base metal thickness of 0.3mm
- 6.S All portal frame members shall be minimum base metal thickness of 0.75mm.
- 7.S All snaptite channels and jambs shall be minimum base metal thickness of 0.42mm
- 8.S All top hats shall be minimum base metal thickness of 1.0mm
- 9.S All portal frame knee and apex plates shall be minimum base metal thickness 1.0mm
- 10.S All screw fasteners shall be Phil Pan Head Zinc Plated #8 x 3/4" (STP0820)
- 11.S All bolt fasteners for anchoring shall be M10 minimum grade 4.6/S
- 12.S Installation of screw fasteners shall generally be undertaken in accordance with the relevant provisions of AS1562.

## Absco Large Gable Roof Shed Notes

### Supporting Slab and Foundations

- 1.F The supporting slab foundation for the garden shed shall be of a minimum size indicated on the installation manual. The top surface of the formed slab shall be level and free of any irregularities which would inhibit the installation of the shed.
- 2.F The structural engineering design for the supporting slab foundation shall be undertaken by a suitably qualified structural engineer. The design shall consider all relevant provisions of AS3600 and AS2870.
- 3.F Between adjacent footings or excavations, the contractor installing the slab foundation shall not exceed a rise of 1 in a run of 2 in line of slope.
- 4.F Unless approved in writing by the slab foundation engineer, the limits of excavations near existing footings shall be in accordance with that indicated below.



The contractor shall undertake investigatory localised excavations near existing footings to ascertain their depth prior to excavating adjacent to them. It is noted that excavating to a depth below that indicated above shall not be undertaken without the written approval from the engineer.

## Absco Sheds Storage Guidelines

- Absco Sheds are designed to be weatherproof for normal weather conditions. In the event of extreme weather conditions such as heavy rain, combined with high wind gusts, the ridge capping, sheeting joints, screw fixings etc., may exhibit minor deformations which may allow some water entry. These areas should be checked regularly to ensure that maximum strength and protection is maintained.
- Other weather conditions such as extreme heat and extreme cold, moist or dry air can influence the effects of concrete floor moisture and/or condensation on the underside of the roof sheets.
- Absco Sheds and storage units are primarily used for storage of garden equipment such as lawnmowers, wheelbarrows, garden tools etc. Storage items that might be adversely affected by any of the above conditions may require additional protection such as being sealed or covered by plastic sheets and/or stacked above the concrete floor on timber slats.
- Waterproof sealants may be used to offer further protection where required around joins and screw fixings, as can rubber door seals and other products which are available from most hardware outlets.
- Placement of waterproof sealants (silicone) between the base of the shed and concrete slab is not recommended, as this process can have a reverse effect, preventing excess water from escaping, resulting with water accumulating and being trapped inside the shed.
- Absco accepts no responsibility for water entry, floor moisture, condensation or the condition of the Contents inside your Absco steel building arising from any of the pre-mentioned weather conditions.
- Absco accepts no responsibility for structural damage if doors were left open and/or not secured during a weather event.

### Post-Installation Care

Clear final product of steel fillings (swarf) caused by drilling holes and tek screws.

Failure to do so may cause discolouration of surfaces and promote corrosion.

Refer to warranty for more details

# Lifetime Warranty Statement



## 1. DEFINITIONS

In this document, capitalised terms have the following meaning:

- (a) "ABSCO" means John Scholtes Investments (No. 1) Pty Ltd trading as Absco Industries.
- (b) "Authorised Purpose" means for storage (other than storage of corrosive materials), and other activities typically expected of a non-habitable structure.
- (c) "Defect" means a defect in the design, workmanship, materials, or any other defect caused by the manufacturing process of the Product (including damaged or missing parts).
- (d) "Excluded Environment" means land located within 1km of:
  - (i) salt marine locations or other areas of marine influence;
  - (ii) severe industrial or other abnormally or highly corrosive environments;
  - (iii) areas not washed by rain;
  - (iv) a recognised flood, bushfire or earthquake zone; or
  - (v) areas with uncontrolled fill, unless an engineered foundation is constructed.
- (e) "Lifetime Warranty Period" means the period of 35 years, commencing on the day after the date of purchase of the Product.
- (f) "Lifetime Warranty Statement" means this 'Lifetime Warranty Statement' document.
- (g) "Parties" means ABSCO and You.
- (h) "Product" means any of following unless stated otherwise in the product description and/or the Product Guide for the Product:
  - (i) products which utilise ABSCO 'SNAP-TITE' technology, including but not limited to garden sheds, chicken coops, bike sheds and bin covers; and
  - (ii) all non-insulated large structures such as carports, awnings, shades and garages,but does not include any product stated to be in the "ABSCO Economy" range.
- (i) "Product Guide" means the guide for installation and maintenance of the Product produced by ABSCO.
- (j) "You" / "Your" means the customer who purchased or installed the Product, or the person who owns the land upon which the Product is installed but does not include a subsequent purchaser of the Product where the Product is moved to a different location to that originally installed.

## 2. ABSCO'S STRUCTURAL WARRANTY

- 2.1. ABSCO provides this warranty to You in relation to the Product. The warranty applies to all colours and finish variants of the Product manufactured by ABSCO and sold by authorised sellers of the Product in Australia or New Zealand.
- 2.2. Subject to the terms of this Lifetime Warranty Statement:
  - (a) ABSCO warrants that the Product will be free from Defects for the duration of the Lifetime Warranty Period; and
  - (b) where the Product contains a Defect, ABSCO will either repair or replace the Product, or provide You with monetary compensation for the Defect in accordance with clause 3.

## 3. WARRANTY CLAIM PROCEDURE

- 3.1. If, during the Lifetime Warranty Period, You believe the Product has a Defect, You must comply with the procedure set out in this clause 3.
- 3.2. Within 30 days of becoming aware of the Defect in the Product, You must notify ABSCO in writing of the alleged Defect ("Defect Notice") by email to [admin@absco.com.au](mailto:admin@absco.com.au).
- 3.3. The Defect Notice must include:
  - (a) Your name, address and contact details;
  - (b) proof of purchase of the Product, including the colour and finish of the Product;
  - (c) the date and location of the installation of the Product and details of the contractor or installer of the Product;
  - (d) details of the alleged Defect in the Product, including but not limited to:
    - (i) a clear description of the alleged Defect;
    - (ii) the date the alleged Defect was first identified; and
    - (iii) any photographs and/or video footage of the alleged Defect.
- 3.4. As soon as reasonably practicable after receipt of the Defect Notice, ABSCO will contact You to investigate the alleged Defect. You must make the Product available to ABSCO and/or its authorised representatives for inspection and testing if so required.
- 3.5. A travel fee may apply if ABSCO and/or its authorised representatives are required to inspect the Product outside a capital metropolitan city area.
- 3.6. If ABSCO's investigations reveal a genuine Defect in the Product, ABSCO may elect to either:
  - (a) repair the Product;
  - (b) replace all or part of the Product; or
  - (c) refund all or part of the purchase price paid by You as compensation for the Defect in the Product.
- 3.7. ABSCO's election in clause 3.6 is at ABSCO's sole discretion.
- 3.8. If ABSCO elects to repair the Product, ABSCO will arrange for a qualified tradesperson to attend to the rectification of the Defect as soon as reasonably practicable. The cost of the repair will be borne by ABSCO.
- 3.9. If ABSCO elects to replace the Product:
  - (a) ABSCO will arrange for the replacement Product to be available for collection by You from the nearest ABSCO authorised reseller as soon as reasonably practicable;
  - (b) You may be required to return the alleged Defective parts or components to ABSCO; and
  - (c) You will be liable for the cost of disassembly and removal of the Product and assembly of the replacement Product.
- 3.10. If ABSCO elects to repair or replace the Product and the necessary parts or components are no longer manufactured or supplied by ABSCO, ABSCO may repair or replace the parts or components with parts or components of a similar quality, grade, composition and colour. You cannot object to such an alternative.
- 3.11. If ABSCO's investigations do not reveal a genuine Defect in the Product (including a defect which is not covered by this warranty), You agree to pay ABSCO's reasonable investigation costs.

#### 4. WARRANTY LIMITATIONS / EXCLUSIONS

- 4.1. To the extent permitted by law, this warranty will not apply where:
- (a) the Product has been installed or used for a purpose that is not an Authorised Purpose;
  - (b) the Product has not been installed, assembled, maintained and/or operated in complete compliance with ABSCO's Product Guide;
  - (c) the Product has been used to store corrosive materials such as fertiliser or chlorine;
  - (d) the Product was installed in excess of 12 months after the purchase of the Product;
  - (e) the Product has not been installed in accordance with the relevant standards, codes and statutory regulations;
  - (f) the Defect is determined to have been caused by storm, wind, rain, earthquake, fire, snow or poor foundations;
  - (g) the Defect is, or is the result of, surface deterioration of panels caused by 'swarf' (tiny particles of steel debris left from cutting, grinding or drilling operations);
  - (h) the Product has been installed in an Excluded Environment;
  - (i) the Product has been subject to accident, negligence, alteration, abuse or misuse;
  - (j) the Defect is determined to be the result of overloading; or
  - (k) ABSCO determines that the Defect is the result of a failure of a third-party product.
- 4.2. You acknowledge that:
- (a) dimensions and colour of the Product are subject to normal manufacturing variations and tolerances, and that reasonable variances are not considered a Defect under this warranty; and
  - (b) this warranty is limited to the repair or replacement of Defects in the Product and does not extend to any other product or any other consequential or indirect damage incurred as a result of the Defect.
- 4.3. For the purpose of this warranty, the following matters are excluded from the definition of Defect:
- (a) general wear and tear which is reasonably expected to occur over the life of the Product;
  - (b) surface deterioration of panels caused by 'swarf' (tiny particles of steel debris left from cutting, grinding or drilling operations);
  - (c) condensation caused by weather conditions such as extreme heat or cold;
  - (d) defects in any fastening apparatus (screws, nuts, bolts, rivets, hasps or bolts);
  - (e) leaks caused by driving rain;
  - (f) improper installation, maintenance or handling of the Product;
  - (g) movement, distortion, collapse or settling of the ground or the supporting structure on which the Product is installed; or
  - (h) staining from foreign substances (including mould, mildew, dirt, grease, oil and any other substance).
- 4.4. To the extent permitted by law, ABSCO is not liable to compensate You for any:
- (a) increased costs or expenses;
  - (b) loss of profit, revenue, business, contracts or anticipated savings;
  - (c) loss or expense resulting from a claim by a third-party; or

- (d) special, indirect or consequential loss or damage of any nature whatsoever, arising from a Defect in the Product or ABSCO's repair or replacement of the Product under this warranty.

#### 5. CONSUMER LAW

##### Australian Consumer Law

- 5.1. Clauses 5.2 to 5.3 apply where the Product was purchased in Australia.
- 5.2. The Product comes with guarantees that cannot be excluded under the Australian Consumer Law. You may be entitled to a replacement or refund for a major failure of the Product and compensation for any other reasonably foreseeable loss or damage. You may also be entitled to have the Product repaired or replaced if the Product fails to be of acceptable quality and the failure does not amount to a major failure.
- 5.3. The benefits of this Lifetime Warranty Statement are in addition to any rights and remedies imposed by Australian State and Federal legislation that cannot be excluded. Nothing in this Lifetime Warranty Statement is to be interpreted as excluding, restricting or modifying any State or Federal legislation applicable to the supply of goods and services which cannot be excluded, restricted or modified.

##### New Zealand Consumer Law

- 5.4. Clauses 5.5 to 5.6 apply where the Product was purchased in New Zealand.
- 5.5. This warranty is subject to the laws of New Zealand, including but not limited to the New Zealand Sale of Goods Act, the Consumer Guarantees Act and the Fair Trading Act.
- 5.6. The benefits of this Lifetime Warranty Statement are in addition to any rights and remedies imposed by New Zealand legislation that cannot be excluded. Nothing in this Lifetime Warranty Statement is to be interpreted as excluding, restricting or modifying any New Zealand legislation applicable to the supply of goods and services which cannot be excluded, restricted or modified.

#### 6. NO REPRESENTATIONS / ENTIRE AGREEMENT

- 6.1. You agree and acknowledge that this Lifetime Warranty Statement contains the entire agreement between the Parties regarding the warranty provided by ABSCO to You in relation to the Product.
- 6.2. To the full extent permitted by law, this Lifetime Warranty Statement supersedes all other warranties of any kind, including whether express or implied by representations, statement, correspondence or other conditions such as merchantability or fitness for purpose.

#### 7. REGISTRATION OF WARRANTY

- 7.1. Please ensure that You keep this Lifetime Warranty Statement in a safe place along with your proof of purchase of the Product.
- 7.2. To ensure ABSCO has a record of your warranty, You can register Your warranty online at <http://absco sheds.com.au/warranty-details/>.